

ROUND TUBE	ASTM A554 / EN 10217-7											
Thickness (mm)	0.8	1.0	1.2	1.5	1.6	2.0	2.3 2.5 2.6	3.0	3.2 3.6	4.0 5.0	6.0	8.0 9.0
O.D. (mm)												
10	□	□	□	□								
12	◎	◎	◎	◎	◎							
13	◎	◎	◎	◎	◎							
14	◎	◎	◎	◎	◎	◎						
15.9 / 16	◎	◎	◎	◎	◎	◎						
18	◎	◎	◎	◎	◎	◎						
19 / 19.05	◎	◎	◎	◎	◎	◎						
20	◎	◎	◎	◎	◎	◎						
21.3	◎	◎	◎	◎	◎	◎	◎	◎				
22	◎	◎	◎	◎	◎	◎	◎	◎				
25 / 25.4	◎	◎	◎	◎	◎	◎	◎	◎				
26.9		◎	◎	◎	◎	◎	◎	◎				
28	◎	◎	◎	◎	◎	◎	◎	◎				
30	◎	◎	◎	◎	◎	◎	◎	◎				
31.8 / 32	◎	◎	◎	◎	◎	◎	◎	◎				
33.7		◎	◎	◎	◎	◎	◎	◎	*	*		
35	◎	◎	◎	◎	◎	◎	◎	◎				
38 / 38.1	◎	◎	◎	◎	◎	◎	◎	◎				
40		◎	◎	◎	◎	◎	◎	◎				
42 / 42.4		◎	◎	◎	◎	◎	◎	◎	*	*		
44.45 / 44.5 / 45		◎	◎	◎	◎	◎	◎	◎				
48.3		◎	◎	◎	◎	◎	◎	◎	*	*		
50.8 / 51		◎	◎	◎	◎	◎	◎	◎				
60.3			◎	◎	◎	◎	◎	◎	*	*		
63.5			◎	◎	◎	◎	◎	◎	*	*		
70			◎	◎	◎	◎	◎	◎	*	*		
76.1 / 76.2			◎	◎	◎	◎	◎	◎	*	*	*	
88.9				◎	◎	◎	◎	◎	*	*	*	
90.0				◎	◎	◎	◎	◎	*	*	*	
101.6				◎	◎	◎	◎	◎	*	*	*	
104.0				◎	◎	◎	◎	◎	*	*	*	
114.3				◎	◎	◎	◎	◎	*	*	*	
127 / 129 / 130				△	△	△	△	△	*	*	*	
139.7				△	△	△	△	△	*	*	*	
154.0				△	△	△	△	△	*	*	*	
168.3						△	△	△	*	*	*	
219.1						△	△	△	*	*	*	
273.0												
323.9												

Surface Finish

: Annealing  
 \* : Brushed / Grit 180  
 □ : Brushed / Grit 180 / 320 / 400

Pickling : Available for above sizes  
 △ : Brushed / Grit 180 / 320  
 ◎ : Brushed / Grit 180 / 320 / 400 / 600